PRODUCT SPECIFICATIONS 300DVBSC(7) Direct Vent System



GLASS VIEWING AREA

27"W x 18"H (486 Square Inches)

TECHNICAL INFORMATION

Max. Btu Input: 21,000 BTU/HR

Ignition System: Signature Command System

Gas Type: Natural or LP Flue Type: T-Lock Pipe

Termination: Rear/Top Vent Convertible

Clearance to Flue for Interior: 3" Top, 1" Bottom and Sides**

Clearance to Flue for Outside Wall: 1'

Clearance to Fireplace: 1/2"

Tavern Brown Firebrick Models: Standing Pilot with Brick and

Blower Factory Installed CSA Design Certified

FIELD INSTALLED ACCESSORIES

Louvers: Polished Brass, Pewter Curved Trim: Brass, Pewter, Black Medium Trim Kit: Brass, Pewter, Black

Variable Thermostat Controlled Forced Air Blower (160 cfm) - BLOT

Fan & Cord: FK12 (160 cfm) FK12 Speed Control: SCVS Tavern Brown firebrick Cottage Red firebrick Mesh Glass Cover

Ambient Technologies[™] Remote Controls and Thermostats

Wood Cabinet Surrounds

Designer Facings

**If vertical rise is 7-1/2 feet or higher when in top vent configuration only, the vent clearance to combustibles is 1" on all sides of the horizontal run.

















