product specifications 500DVBSC(7) Direct Vent System



GLASS VIEWING AREA

33"W x 20 3/8"H (672 Square Inches)

TECHNICAL INFORMATION

Max. Btu Input: 26,000 BTU/HR

Ignition System: Signature Command™ System

Gas Type: Natural or LP Flue Type: T-Lock Pipe

Termination: Rear/Top Vent Convertible

Clearance to Flue for Interior: 3" Top, 1" Bottom and Sides**

Clearance to Flue for Outside Wall: 1"

Clearance to Fireplace: 1/2"

Tavern Brown Firebrick Models: Signature Command with Brick and

Blower Factory Installed CSA Design Certified

FIELD INSTALLED ACCESSORIES

Louvers: Polished Brass, Pewter Curved Trim: Brass, Pewter, Black Medium Trim Kit: Brass, Pewter, Black

Variable Thermostat Controlled Forced Air Blower

(160 cfm) - BLOT

Signature Command Forced Air Blower (160 cfm) - BLOTSC

Fan and Cord: FK12 (160 cfm) (Millivolt only)


FK12 Speed Control: SCVS Tavern Brown firebrick Cottage Red firebrick

Mesh Glass Cover

Ambient Technologies™ Remote Controls and Thermostats

Designer Facings

** If vertical rise is 7-1/2 feet or higher when in top vent configuration only, the vent clearance to combustibles is 1" on all sides of the horizontal run.















1/2" 5/8

2-1/2"

34-3/4

- 20-1/2

41-1/16"

TOP VIEW

- 41-1/16' -- 36" -1-1/4"

<u> 15/16"</u>

5/8"

1/2"

40-1/2

FRAMING DIMENSION

FRONT VIEW





FRAMING DIMENSION

Support

FRAMING

20-3/8" 37-1/2" DIMENSION

Tabs